
Tapered Roller Bearing

32000 Series-32012X/QCL7C





Designacion	**32012X/QCL7C**
Dimensiones principales (mm)	
d1	60
re	95
segundo	23
Basic load ratings（KN）	
dyc(Cr)	95
stc(Cor)	122
Pu	13.4
Speed ratings（rpm）	
Speed Ratings	5300
Limiting Speed	6700
Weight(Kg)	0.59
ISO335	
Dimensions (ABMA)	4CC
Dimensions （mm）	
re	60
d1（	77.8
segundo	23
C	17.5
r1,2(min)	1.5
r3,4(min)	1.5
una	21
Abutment and fillet dimensions （mm）	
da(max)	67
db (min)	67
Da(min)	85
Da (max)	88
Db(min)	91
Ca(min)	4
Cb(min)	5
ra (max)	1.5
rb (max)	1.5
Valor	
e	0.43
Y	1.4
Yo	0.8

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Luoyang Auto Bearing Co.,Ltd-Tel:0598-3607100-Email:moore@lyautobearing.com-http://www.auto-bearing.com