

Tapered Roller Bearing

33000 Series-33016/Q



Designacion	33016/Q
Dimensiones principales (mm)	
d1	80
re	125
segundo	36
Basic load ratings [KN]	
dyc(Cr)	168
stc(Cor)	285
Pu	32
Speed ratings [rpm]	
Speed Ratings	3600
Limiting Speed	5000
Weight(Kg)	1.65
ISO335	
Dimensions (ABMA)	2CE
Dimensions [mm]	
re	80
d1	102
segundo	36
C	29.5
r1,2(min)	1.5
r3,4(min)	1.5
una	26
Abutment and fillet dimensions [mm]	
da(max)	90
db (min)	87
Da(min)	112
Da (max)	117
Db(min)	119
Ca(min)	6
Cb(min)	6.5
ra (max)	1.5
rb (max)	1.5
Valor	
e	0.28
Y	2.1
Yo	1.1

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Luoyang Auto Bearing Co.,Ltd-Tel:0598-3607100-Email:moore@lyautobearing.com-http://www.auto-bearing.com