

## Tapered Roller Bearing

33000 Series-33018/Q



Designacion	<b>33018/Q</b>
Dimensiones principales (mm)	
d1	90
re	140
segundo	39
Basic load ratings [KN]	
dyc(Cr)	216
stc(Cor)	355
Pu	39
Speed ratings [rpm]	
Speed Ratings	3200
Limiting Speed	4500
Weight(Kg)	2.20
ISO335	
Dimensions (ABMA)	2CE
Dimensions [mm]	
re	90
d1	113
segundo	39
C	32.5
r1,2(min)	2
r3,4(min)	1.5
una	27
Abutment and fillet dimensions [mm]	
da(max)	100
db (min)	98
Da(min)	127
Da (max)	132
Db(min)	135
Ca(min)	7
Cb(min)	6.5
ra (max)	2
rb (max)	1.5
Valor	
e	0.27
Y	2.2
Yo	1.3

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Luoyang Auto Bearing Co.,Ltd-Tel:0598-3607100-Email:moore@lyautobearing.com-http://www.auto-bearing.com